

SUITABILITY MATRIX

	sheet offset	reel offset	UV offset	heatset- offset	screen printing	flexo printing	laser ¹	HP Indigo ²	inkjet	UV inkjet
pretex®										
standard	•	•	•	•	•	•	•	• ²		•
manual	•	•	•	•	•	•	•	•		•
Inkjet									•	•
copy + laser	•	•	•	•	•	•	•			•
neobond®										
standard	•	• ³	•		•	•	•	• ⁴		•
super	•	•	•		•	•	•			•
safe	•	•	•		•	•	•			•
go	•	•	•		•		•			
cuturon®										
34 + 47 g/m ²	•	•	•		•	•				
soft	• ⁵	•	• ⁵		• ⁵	•	•			•
X-treme	•	•	•		•		•			

¹ more information in the "laser printability experience list" at www.lahnpaper.de

² except pretex® coloured

³ except neobond® standard white 100 – 150 g/m²

⁴ only neobond® standard white 200 – 220 g/m²

⁵ with interleaving paper for formats 70 x 100 cm

This information is based on our knowledge and experiences in practice. Due to the wide range of influences our products could be exposed to during processing and when they are in use, we recommend subjecting them to your own tests. We reserve the right to make changes due to technical progress or business-related developments. A legally binding assurance of certain properties cannot be derived from the information we provide.



LAHN PAPER GmbH · Auf Brühl 15-27 · 56112 Lahnstein · Germany
T +49 2621 177-0 · F +49 2621 177-609 · www.lahnpaper.de · info@lahnpaper.de

printed on
pretex® 50.100



The mark of
responsible forestry